



Bostik W110

BUTYL ALUMINIUM THERMAL ACOUSTIC WRAP

Date: 17 April 2018

Fact Sheet No.: TDS01916

YOUR SMART ADVANTAGES

- Acoustic tested to ISO 10140-2
- Fire tested
- Self-adhesive meaning quick & easy application

USES

Bostik W110 Thermal Acoustic Wrap is a self-adhesive membrane supplied on a lightweight roll. It is designed for use on plastic rainwater & soil pipes where temperatures do not exceed +90°C. It adheres to many common building materials such as PVC & steelwork.

Bostik W110 is supplied ready to use and does not require time to cure or dry and forms an instant bond around pipework. The butyl adhesive forms a barrier which contains any potential moisture buildup. It is very thin and can be used in tight applications ensuring less room is taken up on site.

No extra banding is required saving installation time and materials on site. It is independently fire and acoustic tested to ensure highest product performance.

Bostik W110 Thermal Acoustic Wrap consists of a thermal acoustic layer laminated between two layers of high-performance pressure sensitive butyl and finished with an aluminium face. The compact and lightweight roll is easy and safe to move around site.

PRODUCT CHARACTERISTICS

Colour	Aluminium finish
Composition	Aluminium film / butyl adhesive / PE foam / butyl adhesive
Product Code	30608627
	Standard length: 5 m
	Standard thickness: 4.0 mm ± 10%
	Standard width: 50 cm

Storage/Shelf Life

At least 12 months from date of manufacture when stored in original unopened packaging in a dry and well ventilated room, within the temperature range +5°C and +30°C. Storage above +50°C may lead to difficulties in removing the release liner when applying. The product is not affected by frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature

+5°C to +40°C

Service Temperature

-30°C to +90°C - depending on operating conditions

Vertical Flow

0 mm (ISO 7390)

Thermal Conductivity (λ)

0,045 W/m.K (DIN 52612)

Fire Certification

Independently tested to BS 476:
Part 6 – Pass
Part 7 – Class 1
Building Regulations: Class 0
See test report for full details.

Acoustic Performance

Independently tested in accordance with ISO 10140-2 weighted sound reduction index of up to 30db (dependent on system design and assembly). For further information and advice contact Technical Services.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik W110 Thermal Acoustic Wrap refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. The surface to be bonded must be clean, dry and free from dust, grease and loose materials.

APPLICATION

2. Unwind the roll and cut a piece to the size required to wrap around the pipe, ensure a minimum 25mm overlap. Start to peel off the protective liner taking care not to touch the adhesive surface. Align the wrap over surface and attach to the surface. While removing the protective liner progressively pull the wrap taut and then press down well over the entire surface.
3. To avoid air bubbles carry out roll-pressing to achieve a good adhesive bond. Ensure that the overlap is well adhered.
4. Use Bostik T303 Self-Adhesive Bright Foil Tape to seal the all the joints.

PRECAUTIONS IN USE

The person carrying out the building work should arrange for sound insulation testing to be carried out by a test body with appropriate third party accreditation. Approved Document E, sections 2, 3, 4 and 6 give examples of constructions which if built correctly should achieve the sound insulation values for dwelling houses and flats. The guidance in these sections is not exhaustive and other designs, materials or products may be used to achieve the required performance.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik W110 Thermal Acoustic Wrap available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com